TP-Link Tapo H100

Technical Datasheet - Reference

Item	Information
Product	TP-Link Tapo H100 Smart IoT Hub with Chime
Connection to router	2.4 GHz Wi-Fi
Accessory radio	Sub-1 GHz; frequency varies by region (EU 868 MHz / US 922 MHz)
Accessory capacity	Up to 64 compatible Tapo sub-devices; actual capacity varies by type
Alarm	Built-in siren up to 90 dB, with selectable ringtones
Power	100-240 V AC, 50/60 Hz
Operating temperature	0 to 40 degrees C
Controls	Status LED; SYNC / Silence button
Dimensions	Depend on region and hardware revision; refer to matching official datasheet

Important: This summary combines model-family information; regional specifications and hardware revisions may differ.

Official sources

https://www.tp-link.com/ae/home-networking/smart-hub/tapo-h100/
https://www.tp-link.com/ae/support/download/tapo-h100/
https://static.tp-link.com/upload/manual/2024/202403/20240307/1910013631_Tapo%20H100_UG.pdf
https://static.tp-link.com/upload/product-overview/2024/202402/20240226/Tapo%20H100%28US%291.0_Datasheet.pdf
https://static.tp-link.com/upload/soho/2025/202511/20251113/8392501231_2025%20Tapo%20Product%20Guide_English_2407_Online.pdf

Independent reference document | Prepared 22 November 2026 | Not issued or endorsed by TP-Link